

**Description**

MS21076 series nut

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[1OAX86A047M11](#)

SKU / Model:	MS21076L04N
Minimum Qty (MOQ):	10
NSN:	5310-01-330-5234
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS21076L04N Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Lubrication:</b>	Dry Film Lubricant
<b>Mounting Hole Diameter:</b>	0.098 Inches Minimum And 0.103 Inches Maximum
<b>Nut Style:</b>	Plate (floating)
<b>Nut Length:</b>	0.651 Inches Maximum
<b>Nut Height:</b>	0.153 Inches Maximum
<b>Plate Thickness:</b>	0.015 Inches Minimum And 0.090 Inches Maximum
<b>Plate Width:</b>	0.275 Inches Minimum And 0.315 Inches Maximum
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.198 Inches Minimum And 0.208 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.404 Inches Minimum And 0.408 Inches Maximum
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjc
<b>Thread Quantity Per Inch:</b>	40
<b>Hardness Rating:</b>	49.0 Rockwell C Maximum
<b>Nominal Thread Size:</b>	0.112 Inches
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5525 Assn Std Single Material Response Overall Or Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall

## How to Order

Order this self-locking nutplate from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/MS21076L04N](https://military-fasteners.com/nuts/self_locking+nutplates/MS21076L04N) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.