

**Description**

Thread: 6-32, self locking nut, two lug, floating, reduced rivet spacing, low height, corrosion resistant steel, silver plated, dry film lube, without eyelets, MS21076 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[1OAX86A067M11](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS21076L06N                               |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5310-00-771-7396                          |
| Schedule B:             | 7318.16.0060                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N MS21076L06N Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3b   |
| <b>Thread Direction:</b>  | Right-hand   |
| <b>Locking Feature:</b>   | Prevailing Torque All Metal Design   |
| <b>Counterbore Diameter:</b>  | 0.178 Inches Minimum Nut And 0.270 Inches Maximum Nut  |
| <b>Lubrication:</b>   | Dry Film Lubricant   |
| <b>Mounting Hole Diameter:</b>  | 0.098 Inches Minimum And 0.103 Inches Maximum  |
| <b>Nut Style:</b>   | Plate  |
| <b>Nut Length:</b>  | 0.682 Inches Maximum   |
| <b>Nut Height:</b>  | 0.171 Inches Maximum   |
| <b>Plate Thickness:</b>   | 0.140 Inches Maximum   |
| <b>Plate Width:</b>   | 0.290 Inches Minimum And 0.357 Inches Maximum  |
| <b>Nut Counterbore Depth:</b>   | 0.140 Inches Nominal Nut   |
| <b>Nut Mounting Provision:</b>  | Straight Holes   |
| <b>Mounting Hole Arrangement Style:</b>                               | 2 Holes  |
| <b>Distance From Aperture Center To Mounting Hole Center:</b>         | 0.213 Inches Minimum And 0.223 Inches Maximum  |
| <b>Center To Center Distance Between Mounting Holes Along Length:</b> | 0.435 Inches Minimum And 0.439 Inches Maximum  |
| <b>Temp Rating:</b>   | 450.0 Deg Fahrenheit Nominal   |
| <b>Thread Series:</b>   | Unjc   |
| <b>Features Provided:</b>   | Floating Nut   |
| <b>Thread Quantity Per Inch:</b>                                      | 32   |
| <b>Nominal Thread Size:</b>   | 0.138 Inches   |
| <b>Material:</b>  | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>                          | Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5525 Assn Std Single Material Response Overall |

## How to Order

Order this self-locking nutplate from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/MS21076L06N](https://military-fasteners.com/nuts/self_locking+nutplates/MS21076L06N) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.