

## P/N MS21076L5N

### **Description**

MS21076 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS21076L5N

Minimum Qty (MOQ): 5

NSN: 5310-01-332-7993

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21076L5N Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.135 Inches Maximum
Nut Length:	1.010 Inches Maximum
Nut Height:	0.328 Inches Nominal
Plate Thickness:	0.032 Inches Nominal
Plate Width:	0.412 Inches Minimum And 0.581 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.364 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.720 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.312 Inches
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5525 Assn Std Single Material Response Overall Or Ams5735 Assn Std Single Material Response Overall

## **How to Order**

Order this self-locking nutplate from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21076L5N">https://military-fasteners.com/nuts/self\_locking+nutplates/MS21076L5N</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.