

Description

MS21077 series nut

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[SNLA069-5](#)

| | |
|-------------------------|---|
| SKU / Model: | MS210775 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5310-00-728-5504 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS21077-5 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque With Nonmetallic Insert |
| Mounting Hole Diameter: | 0.130 Inches Minimum And 0.135 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 1.296 Inches Maximum |
| Nut Height: | 0.283 Inches Minimum And 0.387 Inches Maximum |
| Plate Thickness: | 0.075 Inches Maximum |
| Plate Width: | 0.484 Inches Minimum And 0.609 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.495 Inches Minimum And 0.505 Inches Maximum |
| Center To Center Distance Between Mounting Holes Along Length: | 0.998 Inches Minimum And 1.002 Inches Maximum |
| Temp Rating: | 250.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Features Provided: | Floating Nut |
| Thread Quantity Per Inch: | 24 |
| Hardness Rating: | 36.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.312 Inches |
| Material: | Plastic Polyamide Locking Insert |
| Material: | Steel Nut |
| Surface Treatment: | Cadmium Nut |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Nut |

How to Order

Order this self-locking nutplate from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21077-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.