

**Description**

Thread Size: 7/64", Nut Length: 31/32", Nut Height: 13/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS2107804                                 |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5310-00-726-9072                          |
| Schedule B:             | 7318.16.0085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS21078-04 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3b  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Locking Feature:</b>   | Prevailing Torque With Nonmetallic Insert                 |
| <b>Mounting Hole Diameter:</b>  | 0.098 Inches Minimum And 0.103 Inches Maximum             |
| <b>Nut Style:</b>   | Plate   |
| <b>Nut Length:</b>  | 0.984 Inches Maximum                                      |
| <b>Nut Height:</b>  | 0.133 Inches Minimum And 0.218 Inches Maximum             |
| <b>Plate Thickness:</b>   | 0.075 Inches Maximum                                      |
| <b>Plate Width:</b>   | 0.375 Inches Minimum And 0.406 Inches Maximum             |
| <b>Nut Mounting Provision:</b>  | Straight Holes  |
| <b>Mounting Hole Arrangement Style:</b>                               | 2 Holes   |
| <b>Distance From Aperture Center To Mounting Hole Center:</b>         | 0.339 Inches Minimum And 0.349 Inches Maximum             |
| <b>Center To Center Distance Between Mounting Holes Along Length:</b> | 0.686 Inches Minimum And 0.690 Inches Maximum             |
| <b>Temp Rating:</b>   | 250.0 Deg Fahrenheit Nominal                              |
| <b>Thread Series:</b>   | Unc   |
| <b>Thread Quantity Per Inch:</b>                                      | 40  |
| <b>Hardness Rating:</b>   | 32.0 Rockwell C Maximum                                   |
| <b>Nominal Thread Size:</b>   | 0.112 Inches  |
| <b>Material:</b>  | Plastic Polyamide Locking Insert                          |
| <b>Material:</b>  | Steel Nut   |
| <b>Surface Treatment:</b>   | Cadmium Nut   |
| <b>Surface Treatment Document And Classification:</b>                 | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Nut |

## How to Order

Order this plate - two lug locknut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/MS21078-04](https://military-fasteners.com/nuts/self_locking+nutplates/MS21078-04) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.