

**Description**


thread: 8-32, self locking, two lug, cadmium plated steel, nylon insert, plain rivet holes, MS21078 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS2107808
Minimum Qty (MOQ):	2
NSN:	5310-00-726-9067
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS21078-08 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque With Nonmetallic Insert
<b>Mounting Hole Diameter:</b>	0.098 Inches Minimum And 0.103 Inches Maximum
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	0.984 Inches Maximum
<b>Nut Height:</b>	0.209 Inches Minimum And 0.297 Inches Maximum
<b>Plate Thickness:</b>	0.075 Inches Maximum
<b>Plate Width:</b>	0.375 Inches Minimum And 0.406 Inches Maximum
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.339 Inches Minimum And 0.349 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Length:</b>	0.686 Inches Minimum And 0.690 Inches Maximum
<b>Temp Rating:</b>	250.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unc
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	32.0 Rockwell C Maximum
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Material:</b>	Plastic Polyamide Locking Insert
<b>Material:</b>	Steel Nut
<b>Surface Treatment:</b>	Cadmium Nut
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Nut

## How to Order

Order this self-locking nutplate from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+nutplates/MS21078-08](https://military-fasteners.com/nuts/self_locking+nutplates/MS21078-08) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.