

P/N MS21078-8

Military-Fasteners.com

### Description

Thread: 1/2-20, Thread Size: 1/2", Nut Height: 5/8", Nut Length: 1-5/8

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	MS210788
Minimum Qty (MOQ):	1
NSN:	5310-00-728-6363
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N MS21078-8 Specifications

Thread Class: 3b	
Thread Direction: Right-h	hand
	iling Torque With Nonmetallic Insert
	Inches Minimum And 0.166 Inches Maximum
Nut Style: Plate	
· · ·	Inches Maximum
-	Inches Minimum And 0.609 Inches Maximum
-	Inches Maximum
Plate Width: 0.796 I	Inches Minimum And 0.859 Inches Maximum
Nut Mounting Provision: Straigh	ht Holes
Mounting Hole Arrangement Style: 2 Holes	25
Distance From Aperture Center To Mounting Hole Center: 0.620	Inches Minimum And 0.630 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length: 1.248	Inches Minimum And 1.252 Inches Maximum
Temp Rating: 450.01	Deg Fahrenheit Nominal
Thread Series: Unf	
Thread Quantity Per Inch: 20	
Hardness Rating: 32.0 R	Rockwell C Maximum
Nominal Thread Size: 0.500 I	Inches
Countersink Angle: 88.0 D	Degrees Minimum Nut And 102.0 Degrees Maximum Nut
Material: Plastic	c Polyamide Locking Insert
Material: Steel N	Nut
Surface Treatment: Cadmin	ium Nut
Surface Treatment Document And Classification: Qq-p-4	416,ty 2,cl 3 Fed Spec Single Treatment Response Nut

# How to Order

Order this self-locking nutplate from our inventory online by visiting <u>https://military-fasteners.com/nuts/self\_locking+nutplates/MS21078-8</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.