

## P/N MS21080-5

## **Description**

Thread Size: 1/4", Nut Length: 1-1/4", Nut Height: 3/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS210805

Minimum Qty (MOQ): 1 EA

NSN: 5310-00-728-6370

Schedule B: 7318.16.0085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21080-5 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Mounting Hole Diameter:	0.130 Inches Minimum And 0.135 Inches Maximum
Nut Style:	Plate
Nut Length:	1.250 Inches Maximum
Nut Height:	0.271 Inches Minimum And 0.375 Inches Maximum
Plate Thickness:	0.075 Inches Maximum
Plate Width:	0.500 Inches Minimum And 0.531 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.495 Inches Minimum And 0.505 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.310 Inches Minimum And 0.314 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Hardness Rating:	32.0 Rockwell C Maximum
Nominal Thread Size:	0.312 Inches
Material:	Plastic Polyamide Locking Insert
Material:	Steel Nut
Surface Treatment:	Cadmium Nut
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Nut

### **How to Order**

Order this plate - one lug locknut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21080-5">https://military-fasteners.com/nuts/self\_locking+nutplates/MS21080-5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+nutplates/MS21080-5">https://military-fasteners.com/nuts/self\_locking+nutplates/MS21080-5</a> and selecting the