

Description

1/4-28 thread - self-locking - corner nutplate - cadmium plated steel nylon insert, 250°, - plain rivet holes

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS210814 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5310-00-728-7709 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS21081-4 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque With Nonmetallic Insert |
| Mounting Hole Diameter: | 0.098 Inches Minimum And 0.103 Inches Maximum |
| Nut Style: | Plate |
| Nut Length: | 0.906 Inches Maximum |
| Nut Height: | 0.240 Inches Minimum And 0.375 Inches Maximum |
| Plate Thickness: | 0.075 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Mounting Hole Arrangement Style: | 2 Holes |
| Distance From Aperture Center To Mounting Hole Center: | 0.495 Inches Minimum And 0.505 Inches Maximum |
| Temp Rating: | 250.0 Deg Fahrenheit Nominal |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 28 |
| Hardness Rating: | 32.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.250 Inches |
| Material: | Plastic Polyamide Locking Insert |
| Material: | Steel Nut |
| Surface Treatment: | Cadmium Nut And Chromate Nut |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Nut |

How to Order

Order this self-locking plate nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+nutplates/MS21081-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.