

P/N MS21083B06

Description

Thread Size: 1/8", Nut Height: 9/64", Head Width: 5/16

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS21083B06

Minimum Qty (MOQ): 10

NSN: 5310-00-941-3630

Schedule B: 7415.33.8050

ECCN: EAR99

National Motor Freight: 093460, Bolts / Nuts Noi Bbc / Zinc









P/N MS21083B06 Specifications

| Thread Class: | 3b |
|--|---|
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque With Nonmetallic Insert |
| Lubrication: | Soluble Lubricant |
| Nut Style: | Hexagon |
| Nut Height: | 0.141 Inches Maximum |
| Width Across Flats: | 0.305 Inches Minimum And 0.313 Inches Maximum |
| Temp Rating: | 250.0 Deg Fahrenheit Maximum |
| Thread Series: | Unjc |
| Thread Quantity Per Inch: | 32 |
| Nominal Thread Size: | 0.138 Inches |
| Countersink Angle: | 88.0 Degrees Minimum Nut |
| Bearing Surface Type: | Chamfered Or Washer Faced |
| Bearing Surface Finish: | 125.0 Microinches |
| Material: | Copper Alloy Nut |
| Material: | Plastic Polyamide Locking Insert |
| Surface Treatment: | Cadmium Overall Except Insert And Chromate Overall Except Insert |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall Except Insert |

How to Order

Order this locknut from our inventory online by visiting https://military-fasteners.com/nuts/locknuts/MS21083B06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/locknuts/MS21083B06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/nuts/locknuts/MS21083B06 and selecting the quantity you want then click "add to cart".