

Description

Thread Size: 1/8", Nut Height: 9/64", Head Width: 5/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21083B06
Minimum Qty (MOQ):	10
NSN:	5310-00-941-3630
Schedule B:	7415.33.8050
ECCN:	EAR99
National Motor Freight:	093460, Bolts / Nuts Noi Bbc / Zinc



P/N MS21083B06 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Soluble Lubricant
Nut Style:	Hexagon
Nut Height:	0.141 Inches Maximum
Width Across Flats:	0.305 Inches Minimum And 0.313 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Countersink Angle:	88.0 Degrees Minimum Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Copper Alloy Nut
Material:	Plastic Polyamide Locking Insert
Surface Treatment:	Cadmium Overall Except Insert And Chromate Overall Except Insert
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall Except Insert

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/MS21083B06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.