

**Description**

Thread Size: 1/4", Nut Height: 7/32", Head Width: 27/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21083B4
Minimum Qty (MOQ):	5
NSN:	5310-00-936-9642
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE  
AVAILABLE

## P/N MS21083B4 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque With Nonmetallic Insert
<b>Lubrication:</b>	Soluble Lubricant
<b>Nut Style:</b>	Hexagon
<b>Nut Height:</b>	0.219 Inches Maximum
<b>Width Across Flats:</b>	0.430 Inches Minimum And 0.439 Inches Maximum
<b>Temp Rating:</b>	250.0 Deg Fahrenheit Maximum
<b>Thread Series:</b>	Unf
<b>Thread Quantity Per Inch:</b>	28
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Countersink Angle:</b>	88.0 Degrees Minimum Nut
<b>Bearing Surface Type:</b>	Chamfered Or Washer Faced
<b>Bearing Surface Finish:</b>	125.0 Microinches
<b>Material:</b>	Copper Alloy Nut
<b>Material:</b>	Plastic Polyamide Channel
<b>Surface Treatment:</b>	Cadmium Overall Except Insert And Chromate Overall Except Insert
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall Except Insert

## How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/MS21083B4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.