

**Description**

Thread Size: 3/8", Nut Height: 9/32", Head Width: 35/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS21083B6
Minimum Qty (MOQ):	10 EA
NSN:	5310-00-926-5832
Schedule B:	7415.33.8050
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS21083B6 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque With Nonmetallic Insert
<b>Nut Style:</b>	Hexagon
<b>Nut Height:</b>	0.282 Inches Maximum
<b>End Item Identification:</b>	Trident Hull Structure;mk 28, 5-inch 38 Caliber Twin Gun Mount;bridge Armor Vehicle (avlb) - Model M60a1;helicopter Observation (ahip), Oh-58d;fms - Aircraft, Orion P-3;submarine Auxillary And Miscellaneous Systems;los Angeles Class Ssn (688);armored Vehicle Launch Bridge (m60a1 & M48a5);helicopter, Kiowa Oh-58 A&c
<b>Width Across Flats:</b>	0.553 Inches Minimum And 0.564 Inches Maximum
<b>Temp Rating:</b>	250.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjf
<b>Thread Quantity Per Inch:</b>	24
<b>Nominal Thread Size:</b>	0.375 Inches
<b>Countersink Angle:</b>	88.0 Degrees Nominal Nut
<b>Bearing Surface Type:</b>	Chamfered Or Washer Faced
<b>Bearing Surface Finish:</b>	125.0 Microinches
<b>Material:</b>	Copper Alloy Nut
<b>Material:</b>	Plastic Polyamide Locking Insert
<b>Surface Treatment:</b>	Cadmium Overall Except Insert
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Except Insert

## How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/MS21083B6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.