

Description

Thread: 8-32, self locking, hexagon, low height, corrosion resistant stainless steel, nylon insert, passivated, MS21083 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21083C08
Minimum Qty (MOQ):	25
NSN:	5310-00-939-0850
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS21083C08 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Soluble Lubricant
Nut Style:	Hexagon
Nut Height:	0.188 Inches Maximum
End Item Identification:	W/s:stream (std. Tensioned Replenishment At Sea Method); Fire Control System, Missile Mk74 (fcs); Support Equipment, B-1 Aircraft; Guided Missile Launching System, Mk 26 (gmls); Airborne Mobile Dir Air Spt Ctl (2id), (02m Jul83)(an/uyq-3a); Support Equipment, B-52 Aircraft; Radar Set, An/tpn-18; Aircraft, Sof (ac-130h, Mc-130h, Ec-130e, Hc-130); Communications Terminal, Satellite An/gsc-39(v)1
Width Across Flats:	0.336 Inches Minimum And 0.345 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Countersink Angle:	88.0 Degrees Minimum Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Plastic Polyamide Locking Insert
Material:	Steel Corrosion Resisting Nut
Surface Treatment:	Passivate Nut
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall Except Insert

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21083C08 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.