

**Description**

Thread Size: 5/8", Nut Height: 27/64", Head Width: 15/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[L79NTE1018](#)

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS21083C10                                |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5310-00-050-9372                          |
| Schedule B:             | 7318.16.0085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS21083C10 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3b   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Locking Feature:</b>                               | Prevailing Torque With Nonmetallic Insert                        |
| <b>Lubrication:</b>                                   | Soluble Lubricant  |
| <b>Nut Style:</b>                                     | Hexagon  |
| <b>Nut Height:</b>                                    | 0.407 Inches Maximum   |
| <b>Width Across Flats:</b>                            | 0.928 Inches Minimum And 0.940 Inches Maximum                    |
| <b>Temp Rating:</b>                                   | 250.0 Deg Fahrenheit Maximum                                     |
| <b>Thread Series:</b>                                 | Unjf   |
| <b>Thread Quantity Per Inch:</b>                      | 18   |
| <b>Nominal Thread Size:</b>                           | 0.625 Inches   |
| <b>Countersink Angle:</b>                             | 88.0 Degrees Minimum Nut   |
| <b>Bearing Surface Type:</b>                          | Chamfered Or Washer Faced  |
| <b>Bearing Surface Finish:</b>                        | 125.0 Microinches  |
| <b>Material:</b>                                      | Plastic Polyamide Locking Insert                                 |
| <b>Material:</b>                                      | Steel Corrosion Resisting Nut                                    |
| <b>Surface Treatment:</b>                             | Passivate Overall Except Insert                                  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall Except Insert |

## How to Order

Order this self-locking hexagon nut from our inventory online by visiting [https://military-fasteners.com/nuts/self\\_locking+hexagon+nuts/MS21083C10](https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21083C10) and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.