

Description

Thread Size: 5/8", Nut Height: 27/64", Head Width: 15/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[L79NTE1018](#)

SKU / Model:	MS21083C10
Minimum Qty (MOQ):	5
NSN:	5310-00-050-9372
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21083C10 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Soluble Lubricant
Nut Style:	Hexagon
Nut Height:	0.407 Inches Maximum
Width Across Flats:	0.928 Inches Minimum And 0.940 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	18
Nominal Thread Size:	0.625 Inches
Countersink Angle:	88.0 Degrees Minimum Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Plastic Polyamide Locking Insert
Material:	Steel Corrosion Resisting Nut
Surface Treatment:	Passivate Overall Except Insert
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall Except Insert

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21083C10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.