

# P/N MS21083C4

## **Description**

thread: 1/4-28, self-locking, hexagon, low height, corrosion resistant steel, nylon insert, passivated

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

### **Additional Information**

#### **Alternate Part Numbers**

## L79NTE0428

SKU / Model: MS21083C4

Minimum Qty (MOQ): 25

NSN: 5310-00-897-6145

Schedule B: 7415.33.8050

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21083C4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Nut Style:	Hexagon
Nut Height:	0.219 Inches Maximum
Width Across Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unjf
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Countersink Angle:	88.0 Degrees Nominal Nut
Criticality Code Justification:	Feat
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Special Features:	Weapon System Essential
Material:	Plastic Polyamide Locking Insert
Material:	Steel Corrosion Resisting Overall Except Insert
Surface Treatment:	Passivate Overall Except Insert
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall Except Insert

## **How to Order**

Order this self-locking hexagon nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self-locking+hexagon+nuts/MS21083C4">https://military-fasteners.com/nuts/self-locking+hexagon+nuts/MS21083C4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.