

## P/N MS21083C5

### **Description**

thread: 5/16-24, self locking, hexagon, low height, corrosion resistant steel, nylon insert, passivated, MS21083 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

#### MS21083-C5

SKU / Model: MS21083C5

Minimum Qty (MOQ): 25

NSN: 5310-00-020-3260

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







<sup>\*</sup> See page 2 for technical characteristics

# **P/N MS21083C5 Specifications**

| Thread Class:                                  | 3b   |
|--|--|
| Thread Direction:                              | Right-hand   |
| Locking Feature:                               | Prevailing Torque With Nonmetallic Insert                        |
| Lubrication:                                   | Soluble Lubricant  |
| Nut Style:                                     | Hexagon  |
| Nut Height:                                    | 0.266 Inches Maximum   |
| Width Across Flats:                            | 0.492 Inches Minimum And 0.502 Inches Maximum                    |
| Temp Rating:                                   | 250.0 Deg Fahrenheit Maximum                                     |
| Thread Series:                                 | Unjf   |
| Thread Quantity Per Inch:                      | 24   |
| Nominal Thread Size:                           | 0.312 Inches   |
| Countersink Angle:                             | 88.0 Degrees Minimum Nut   |
| Bearing Surface Type:                          | Chamfered Or Washer Faced  |
| Bearing Surface Finish:                        | 125.0 Microinches  |
| Material:                                      | Plastic Polyamide Locking Insert                                 |
| Material:                                      | Steel Corrosion Resisting Nut                                    |
| Surface Treatment:                             | Passivate Overall Except Insert                                  |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall Except Insert |

## **How to Order**

Order this self-locking hexagon nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21083C5">https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21083C5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21083C5">https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21083C5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21083C5">https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21083C5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21083C5">https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21083C5</a> and selecting the properties of the properti