

P/N MS21083C5

Military-Fasteners.com

Description

thread: 5/16-24, self locking, hexagon, low height, corrosion resistant steel, nylon insert, passivated, MS21083 series nut

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

Alternate Part Numbers

| MS21083-C5 | |
|-------------------------|---|
| SKU / Model: | MS21083C5 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5310-00-020-3260 |
| Schedule B: | 7318.16.0085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21083C5 Specifications

| Thread Class: | 3b |
|--|--|
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque With Nonmetallic Insert |
| Lubrication: | Soluble Lubricant |
| Nut Style: | Hexagon |
| Nut Height: | 0.266 Inches Maximum |
| Width Across Flats: | 0.492 Inches Minimum And 0.502 Inches Maximum |
| Temp Rating: | 250.0 Deg Fahrenheit Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 24 |
| Nominal Thread Size: | 0.312 Inches |
| Countersink Angle: | 88.0 Degrees Minimum Nut |
| Bearing Surface Type: | Chamfered Or Washer Faced |
| Bearing Surface Finish: | 125.0 Microinches |
| Material: | Plastic Polyamide Locking Insert |
| Material: | Steel Corrosion Resisting Nut |
| Surface Treatment: | Passivate Overall Except Insert |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall Except Insert |

How to Order

Order this self-locking hexagon nut from our inventory online by visiting <u>https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21083C5</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.