

P/N MS21083C7

Military-Fasteners.com

Description

thread: 7/16-20, self locking nut, hexagon, low height, corrosion resistant steel, nylon insert, passivated

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

| SKU / Model: | MS21083C7 |
|-------------------------|-------------------------------------------|
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-00-074-2328 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS21083C7 Specifications

| Thread Class: | 3b |
|------------------------------------------------|------------------------------------------------------------------|
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque With Nonmetallic Insert |
| Lubrication: | Soluble Lubricant |
| Nut Style: | Hexagon |
| Nut Height: | 0.328 Inches Maximum |
| Width Across Flats: | 0.679 Inches Minimum And 0.690 Inches Maximum |
| Temp Rating: | 250.0 Deg Fahrenheit Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 20 |
| Nominal Thread Size: | 0.438 Inches |
| Countersink Angle: | 88.0 Degrees Minimum Nut |
| Bearing Surface Type: | Chamfered Or Washer Faced |
| Bearing Surface Finish: | 125.0 Microinches |
| Material: | Plastic Polyamide Locking Insert |
| Material: | Steel Corrosion Resisting Nut |
| Surface Treatment: | Passivate Overall Except Insert |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall Except Insert |

How to Order

Order this self-locking hexagon nut from our inventory online by visiting <u>https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21083C7</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out<u>here</u> to complete your order.