

Description

Thread Size: 7/64", Nut Height: 1/8", Head Width: 15/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21083D04
Minimum Qty (MOQ):	50
NSN:	5310-00-939-1031
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



P/N MS21083D04 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Soluble Lubricant
Nut Style:	Hexagon
Nut Height:	0.125 Inches Maximum
Width Across Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Thread Quantity Per Inch:	40
Nominal Thread Size:	0.112 Inches
Countersink Angle:	88.0 Degrees Minimum Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Aluminum Nut
Material:	Plastic Polyamide Locking Insert
Surface Treatment:	Anodize Overall Except Insert Or Chromate Overall Except Insert
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Except Insert Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall Except Insert

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/MS21083D04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.