

Description


thread: 6-32, self-locking, hexagon, low height, aluminum alloy, nylon insert, anodized, MS21083 series nut

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21083D06
Minimum Qty (MOQ):	25
NSN:	5310-00-921-3857
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



P/N MS21083D06 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Soluble Lubricant
Nut Style:	Hexagon
Nut Height:	0.141 Inches Maximum
Width Across Flats:	0.305 Inches Minimum And 0.313 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Countersink Angle:	88.0 Degrees Minimum Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Aluminum Alloy Nut
Material:	Plastic Polyamide Locking Insert
Surface Treatment:	Anodize Overall Except Insert Or Chromate Overall Except Insert
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Except Insert Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall Except Insert

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21083D06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.