

Description

thread: 1/4-28, self-locking nut, hexagon, low height, aluminum alloy, nylon insert, anodized

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21083D4
Minimum Qty (MOQ):	10
NSN:	5310-00-922-9081
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N MS21083D4 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Soluble Lubricant
Nut Style:	Hexagon
Nut Height:	0.219 Inches Maximum
End Item Identification:	Sonar Sets, An/bqs-14a/15;arleigh Burke Class Ddg;aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130);aircraft, Osprey V-22a, Marine Corps;aircraft, Airlifter C-17a;surface Minesweeping Systems;los Angeles Class Ssn (688);engine, Aircraft, Tf-33-p-7 (c-141a/b);aircraft, Osprey V-22a, Air Force;ah-64-d Longbow; Ticonderoga Class Cg (47);fms - Build Frigates Class Ships
Width Across Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	28
Nominal Thread Size:	0.250 Inches
Countersink Angle:	88.0 Degrees Minimum Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Aluminum Alloy Nut
Material:	Plastic Polyamide Locking Insert
Surface Treatment:	Anodize Overall Except Insert Or Chromate Overall Except Insert
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Except Insert Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall Except Insert

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21083D4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.