

Description

Thread: 3/8-24, self-locking nut, hexagon, low height, aluminum alloy, nylon insert, anodized

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21083D6
Minimum Qty (MOQ):	10
NSN:	5310-00-926-1851
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



P/N MS21083D6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Dry Film Lubricant
Nut Style:	Hexagon
Nut Height:	0.282 Inches Maximum
End Item Identification:	Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130);ticonderoga Class Cg (47); Helicopter Observation (ahip), Oh-58d;f-22 Raptor Air Dominance Fighter;deck Machinery;guided Missile, Intercept;aircraft Black Hawk (mh-60k Special Operations Aircraft);torpedo, Adcap 48;aircraft Mh-47e Special Operations Aircraft;surface Minesweeping Systems;ah-64-d Longbow
Width Across Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Countersink Angle:	88.0 Degrees Minimum Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Aluminum Alloy Nut
Material:	Plastic Polyamide Locking Insert
Surface Treatment:	Anodize Overall Except Insert Or Chromate Overall Except Insert
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec 1st Treatment Response Overall Except Insert Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall Except Insert

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21083D6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.