

P/N MS21083N06

Description

thread: 6-32, self locking, hexagon, low height, cadmium plated steel, nylon insert, locknut, MS21083 series nut

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS21083N06

Minimum Qty (MOQ): 50

NSN: 5310-00-905-8451

Schedule B: 7318.16.0085


ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS21083N06 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Soluble Lubricant
Nut Style:	Hexagon
Nut Height:	0.141 Inches Maximum
Width Across Flats:	0.305 Inches Minimum And 0.313 Inches Maximum
Temp Rating:	350.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Hardness Rating:	35.0 Rockwell C Maximum
Nominal Thread Size:	0.138 Inches
Countersink Angle:	88.0 Degrees Minimum Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Plastic Polyamide Locking Insert
Material:	Steel Nut
Surface Treatment:	Cadmium Overall Except Insert And Chromate Overall Except Insert
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Except Insert

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21083N06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.