

# P/N MS21083N08

### **Description**

thread: 8-32, self locking, hexagon, low height, cadmium plated steel, nylon insert, MS21083 series nut

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS21083N08

Minimum Qty (MOQ): 100

NSN: 5310-00-941-6019

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS21083N08 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Soluble Lubricant
Nut Style:	Hexagon
Nut Height:	0.188 Inches Maximum
lii End Item Identification:	Mrap - Cougar Tow; Mrap - Cougar Sabr/tow
Width Across Flats:	0.336 Inches Minimum And 0.345 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Maximum
Thread Series:	Unjc
Thread Quantity Per Inch:	32
Hardness Rating:	35.0 Rockwell C Maximum
Nominal Thread Size:	0.164 Inches
Countersink Angle:	88.0 Degrees Minimum Nut
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Plastic Polyamide Locking Insert
Material:	Steel Nut
Surface Treatment:	Cadmium Overall Except Insert And Chromate Overall Except Insert
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Except Insert

## **How to Order**

Order this self-locking hexagon nut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21083N08">https://military-fasteners.com/nuts/self\_locking+hexagon+nuts/MS21083N08</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.