

Description

thread: 3/4-16, self-locking nut - hexagon, low height - cadmium plated steel nylon insert, 250°,

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS21083N12 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5310-00-939-0783 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS21083N12 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque With Nonmetallic Insert |
| Lubrication: | Soluble Lubricant |
| Nut Style: | Hexagon |
| Nut Height: | 0.422 Inches Maximum |
| Width Across Flats: | 1.052 Inches Minimum And 1.064 Inches Maximum |
| Temp Rating: | 250.0 Deg Fahrenheit Maximum |
| Thread Series: | Unjf |
| Thread Quantity Per Inch: | 16 |
| Hardness Rating: | 35.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.750 Inches |
| Countersink Angle: | 88.0 Degrees Minimum Nut |
| Bearing Surface Type: | Chamfered Or Washer Faced |
| Bearing Surface Finish: | 125.0 Microinches |
| Material: | Plastic Polyamide Locking Insert |
| Material: | Steel Nut |
| Surface Treatment: | Cadmium Overall Except Insert And Chromate Overall Except Insert |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec All Treatment Responses Overall Except Insert |

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS21083N12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.