

Description

Thread Size: 7/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS21084L07 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5310-01-057-0609 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



NO IMAGE
AVAILABLE

P/N MS21084L07 Specifications

| | |
|---|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Washer Outside Diameter: | 0.773 Inches Maximum |
| Lubrication: | Dry Film Lubricant |
| Overall Height: | 0.500 Inches Maximum |
| Nut Style: | Double Hexagon |
| Washer Thickness: | 0.053 Inches Minimum |
| Temp Rating: | 450.0 Deg Fahrenheit Maximum |
| Thread Series: | Unf |
| Thread Quantity Per Inch: | 20 |
| Hardness Rating: | 48.0 Rockwell C Maximum |
| Nominal Thread Size: | 0.438 Inches |
| Special Features: | Wrenching Facility Per Ms33787-18 |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/MS21084L07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.