



Military-Fasteners.com

P/N MS21086L3K

Description

Thread Size: 1/4", Nut Length: 1/2", Nut Height: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21086L3K
Minimum Qty (MOQ):	20 EA
NSN:	5310-01-187-9070
Schedule B:	7318.16.0085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N MS21086L3K Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Counterbore Diameter:	0.194 Inches Minimum Nut
Lubrication:	Dry Film Lubricant
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.521 Inches Maximum
Nut Height:	0.250 Inches Maximum
Plate Thickness:	0.047 Inches Maximum
Plate Width:	0.298 Inches Minimum And 0.328 Inches Maximum
Nut Counterbore Depth:	0.062 Inches Minimum Nut
Nut Mounting Provision:	Dimpled Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Aperture Center To Mounting Hole Center:	0.245 Inches Minimum And 0.255 Inches Maximum
Center To Center Distance Between Mounting Holes Along Width:	0.217 Inches Minimum And 0.221 Inches Maximum
Temp Rating:	450.0 Deg Fahrenheit Nominal
Thread Series:	Unf
Thread Quantity Per Inch:	32
Hardness Rating:	49.0 Rockwell C Maximum
Nominal Thread Size:	0.190 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Fed Spec Single Treatment Response Overall

How to Order

Order this plate - one lug locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/MS21086L3K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.