

**Description**

Thread Size: 3/8", Nut Length: 7/8", Nut Height: 3/8",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21086L6
Minimum Qty (MOQ):	1
NSN:	5310-00-760-7225
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS21086L6 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Counterbore Diameter:</b>	0.379 Inches Minimum Nut
<b>Lubrication:</b>	Dry Film Lubricant
<b>Mounting Hole Diameter:</b>	0.130 Inches Minimum And 0.135 Inches Maximum
<b>Nut Style:</b>	Plate
<b>Nut Length:</b>	0.856 Inches Maximum
<b>Nut Height:</b>	0.344 Inches Maximum
<b>Plate Thickness:</b>	0.075 Inches Maximum
<b>Plate Width:</b>	0.580 Inches Minimum And 0.614 Inches Maximum
<b>Nut Counterbore Depth:</b>	0.062 Inches Minimum Nut
<b>Nut Mounting Provision:</b>	Straight Holes
<b>Mounting Hole Arrangement Style:</b>	2 Holes
<b>Distance From Aperture Center To Mounting Hole Center:</b>	0.409 Inches Minimum And 0.419 Inches Maximum
<b>Center To Center Distance Between Mounting Holes Along Width:</b>	0.267 Inches Minimum And 0.271 Inches Maximum
<b>Temp Rating:</b>	450.0 Deg Fahrenheit Nominal
<b>Thread Series:</b>	Unjf
<b>Thread Quantity Per Inch:</b>	24
<b>Hardness Rating:</b>	49.0 Rockwell C Maximum
<b>Nominal Thread Size:</b>	0.375 Inches
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall

## How to Order

Order this self-locking nutplate from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/MS21086L6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.