

P/N MS21090-0623

Description

Fastener Length: 7/16", Thread: 6-32, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS210900623

Minimum Qty (MOQ): 20 EA

NSN: 5305-00-459-1172

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS21090-0623 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.407 Inches Minimum And 0.438 Inches Maximum
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Locking Feature:	Pellet Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Qq-s-634 Fed Spec Single Material Response Overall Or Qq-s-637 Fed Spec Single Material Response Overall Or 66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 9c Style

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS21090-0623 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.