

Description

Fastener Length: 5/8", Thread: 6-32, Thread Length: 17/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS210900625
Minimum Qty (MOQ):	50
NSN:	5305-00-052-1545
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21090-0625 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.528 Inches Minimum And 0.538 Inches Maximum
Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Astm A576 Assn Std Single Material Response Overall Or Astm A108 Assn Std Single Material Response Overall Or Qq-s-637 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS21090-0625> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.