

**Description**

Fastener Length: 3/4", Thread: 6-32, Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS210900626
Minimum Qty (MOQ):	40 EA
NSN:	5305-00-182-9451
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS21090-0626 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.657 Inches Minimum And 0.750 Inches Maximum
<b>Fastener Length:</b>	0.719 Inches Minimum And 0.750 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.256 Inches Minimum And 0.270 Inches Maximum
<b>Head Height:</b>	0.087 Inches Minimum And 0.097 Inches Maximum
<b>Locking Feature:</b>	Patch Threads Or Pellet Threads Or Strip Threads
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	60000 Pounds Per Square Inch
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	66 Fed Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type 2 Class 3 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	3 Type And 9c Style

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS21090-0626> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.