

Description

Fastener Length: 1-29/32", Thread: 6-32, Thread Length: 1-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS210900632
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-099-3149
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS21090-0632 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.938 Inches Minimum And 2.000 Inches Maximum
Fastener Length:	1.903 Inches Minimum And 1.913 Inches Maximum
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Fed-std-66 Fed Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,typeii,class3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type Or 9c Style

How to Order

Order this screwlock from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS21090-0632> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.