



Military-Fasteners.com

P/N MS21090-0835

Description

Fastener Length: 5/16", Thread: 8-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS210900835
Minimum Qty (MOQ):	30 EA
NSN:	5305-00-455-2705
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21090-0835 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.219 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Locking Feature:	Pellet Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Material:	Steel Comp 1010 Overall Or Steel Comp 1015 Overall Or Steel Comp 1016 Overall Or Steel Comp 1018 Overall Or Steel Comp 1019 Overall Or Steel Comp 1020 Overall Or Steel Comp 1022 Overall Or Steel Comp 1025 Overall Or Steel Comp 1026 Overall Or Steel Comp 1035 Overall Or Steel Comp 1040 Overall Or Steel Comp 1042 Overall Or Steel Comp 1045 Overall Or Steel Comp 1046 Overall Or Steel Comp 1548 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 9c Style
Departure From Cited Designator:	As Mod By Locking Element

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS21090-0835> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.