

P/N MS21090-0840

Description

Fastener Length: 3/4", Thread: 8-32, Thread Length: 41/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS210900840

Minimum Qty (MOQ): 10 EA

NSN: 5305-00-078-0246

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS21090-0840 Specifications

| Thread Class: | 2a |
|--|--|
| | |
| Thread Direction: | Right-hand |
| Thread Length: | 0.635 Inches Minimum And 0.645 Inches Maximum |
| Fastener Length: | 0.719 Inches Minimum And 0.750 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.306 Inches Minimum And 0.322 Inches Maximum |
| Head Height: | 0.105 Inches Minimum And 0.115 Inches Maximum |
| Locking Feature: | Patch Threads Or Pellet Threads Or Strip Threads |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Material Document And Classification: | Astm A576 Assn Std Single Material Response Overall Or Astm A108 Assn Std Single Material Response Overall Or Qq-s-637 Fed Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty2,class 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this screwlock from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/MS21090-0840 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.