

Description

Fastener Length: 7/8", Thread: 8-32, Thread Length: 53/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS210900841
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-078-0229
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS21090-0841 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.781 Inches Minimum And 0.843 Inches Maximum
Fastener Length:	0.843 Inches Minimum And 0.875 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Material:	Steel Overall
Material Document And Classification:	Astm A576 Assn Std Single Material Response Overall Or Astm A108 Assn Std Single Material Response Overall Or Qq-s-637 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screwlock from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS21090-0841> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.