



Military-Fasteners.com

P/N MS21090-348

Description

Fastener Length: 5/16", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21090348
Minimum Qty (MOQ):	85 EA
NSN:	5305-01-101-0715
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21090-348 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.219 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Material:	Plastic Locking Feature
Material:	Steel Fastener
Material Document And Classification:	66 Fed Std Single Material Response Fastener
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS21090-348> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.