

## P/N MS21090-689

## **Description**

Fastener Length: 1/2", Thread: 3/8-24, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS21090689

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-455-2762

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS21090-689 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Pan
Head Diameter:	0.716 Inches Minimum And 0.740 Inches Maximum
Head Height:	0.244 Inches Minimum And 0.261 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And 9c Style

### **How to Order**

Order this self locking screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/MS21090-689">https://military-fasteners.com/screws/socket+head+cap+screws/MS21090-689</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.