

**Description**

Fastener Length: 1/2", Thread: 3/8-24, Thread Length: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS21090689
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-455-2762
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS21090-689 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.469 Inches Minimum And 0.500 Inches Maximum
<b>Fastener Length:</b>	0.469 Inches Minimum And 0.500 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.716 Inches Minimum And 0.740 Inches Maximum
<b>Head Height:</b>	0.244 Inches Minimum And 0.261 Inches Maximum
<b>Locking Feature:</b>	Strip Threads
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	60000 Pounds Per Square Inch
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf
<b>Nondefinitive Spec/std Data:</b>	3 Type And 9c Style

## How to Order

Order this self locking screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS21090-689> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.