

Description

Fastener Length: 5/16", Thread: 2-56, Thread Length: 17/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS210930203 |
| Minimum Qty (MOQ): | 30 EA |
| NSN: | 5305-00-196-5395 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS21093-0203 Specifications

| | |
|----------------------------------|--|
| Thread Class: | 2a |
| Thread Length: | 0.202 Inches Minimum And 0.280 Inches Maximum |
| Fastener Length: | 0.281 Inches Minimum And 0.312 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.150 Inches Minimum And 0.182 Inches Maximum |
| Locking Feature: | Patch Or Pellet Or Strip |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.086 Inches |
| Thread Quantity Per Inch: | 56 |
| Minimum Tensile Strength: | 60000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Thread Series Designator: | Unc |

How to Order

Order this screwlock from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS21093-0203> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.