

Description

Fastener Length: 5/16", Thread: 4-40, Thread Length: 17/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS210930410
Minimum Qty (MOQ):	20
NSN:	5305-00-726-1239
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS21093-0410 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.264 Inches Minimum And 0.272 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.200 Inches Minimum And 0.225 Inches Maximum
Head Height:	0.040 Inches Minimum And 0.048 Inches Maximum
Locking Feature:	Pellet Or Strip Or Patch
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS21093-0410> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.