



★ FASTENERS

Military-Fasteners.com

P/N MS21093-0836

Description


Fastener Length: 3/4", Thread: 8-32, Thread Length: 11/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS210930836
Minimum Qty (MOQ):	50
NSN:	5305-00-174-4601
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21093-0836 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.585 Inches Minimum And 0.688 Inches Maximum
Fastener Length:	0.719 Inches Minimum And 0.750 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.300 Inches Minimum And 0.332 Inches Maximum
Locking Feature:	Pellet Or Strip Or Patch
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 1010 Or Steel Comp 1011 Or Steel Comp 1013
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 3c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS21093-0836> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.