

P/N MS21094-3003

Description

Fastener Length: 37/64", Thread: 10-32, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS210943003

Minimum Qty (MOQ): 5 EA

NSN: 5306-00-194-3677

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS21094-3003 Specifications

Thread Direction: Right-hand Thread Length: 0.381 Inches Minimum And 0.447 Inches Maximum Fastener Length: 0.578 Inches Minimum And 0.624 Inches Maximum Head Style: Hexagon Head Height: 0.109 Inches Minimum And 0.141 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Locking Feature: Patch Threads Or Pellet Threads Or Strip Threads Nominal Thread Diameter: 0.190 Inches Grip Length: 0.177 Inches Minimum And 0.197 Inches Maximum Locking Feature Provided: Inished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 1.25000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Material: Plastic Polyamide Locking Feature Material: Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 4037 Fastener Material: Steel Comp 4140 Fastener Or Steel Comp 4037 Fastener Material Document And Classification: Mil-f-18240 Mil Spec Single Material Response Locking Feature Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Unf	Thread Class:	3a
Thread Length: 0.381 Inches Minimum And 0.447 Inches Maximum Fastener Length: 0.578 Inches Minimum And 0.624 Inches Maximum Head Style: Hexagon Head Height: 0.109 Inches Minimum And 0.141 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Locking Feature: Patch Threads Or Pellet Threads Or Strip Threads Nominal Thread Diameter: 0.190 Inches Grip Length: 0.177 Inches Minimum And 0.197 Inches Maximum Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Material: Plastic Polyamide Locking Feature Material: Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 4130 Fastener Or Steel Comp 4037 Fastener Material Document And Classification: Wilf-Ti8240 Mill Spec Single Material Response Locking Feature Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Q-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener		
Fastener Length: 0.578 Inches Minimum And 0.624 Inches Maximum Head Style: Hexagon Head Height: 0.109 Inches Minimum And 0.141 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Locking Feature: Patch Threads Or Pellet Threads Or Strip Threads Nominal Thread Diameter: 0.190 Inches Grip Length: 0.177 Inches Minimum And 0.197 Inches Maximum Features Provided: Inished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Material: Plastic Polyamide Locking Feature Material: Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8630 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 4130 Fastener Or Steel Comp 4037 Fastener Material Document And Classification: Mil-f-18240 Mil Spec Single Material Response Locking Feature Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Q-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener		
Head Style: Hexagon Head Height: 0.109 Inches Minimum And 0.141 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Locking Feature: Patch Threads Or Pellet Threads Or Strip Threads Nominal Thread Diameter: 0.190 Inches Grip Length: 0.177 Inches Minimum And 0.197 Inches Maximum Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Material: Plastic Polyamide Locking Feature Material: Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 835 Fastener Or Steel Comp 4130 Fastener Or Steel Comp 4037 Fastener Material Document And Classification: Steel Overall Milf-18240 Mil Spec Single Material Response Locking Feature Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener	Thread Length:	0.381 Inches Minimum And 0.447 Inches Maximum
Head Height: 0.109 Inches Minimum And 0.141 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Locking Feature: Patch Threads Or Pellet Threads Or Strip Threads Nominal Thread Diameter: 0.190 Inches Grip Length: 0.177 Inches Minimum And 0.197 Inches Maximum Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Material: Plastic Polyamide Locking Feature Material: Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 4130 Fastener Or Steel Comp 4037 Fastener Material: Steel Overall Material Document And Classification: Mil-f-18240 Mil Spec Single Material Response Locking Feature Surface Treatment Document And Classification: Q-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener	Fastener Length:	0.578 Inches Minimum And 0.624 Inches Maximum
Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Locking Feature: Patch Threads Or Pellet Threads Or Strip Threads Nominal Thread Diameter: 0.190 Inches Grip Length: 0.177 Inches Minimum And 0.197 Inches Maximum Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Material: Plastic Polyamide Locking Feature Material: Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8630 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 4130 Fastener Or Steel Comp 4037 Fastener Material: Steel Overall Material Document And Classification: Mil-f-18240 Mil Spec Single Material Response Locking Feature Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener	Head Style:	Hexagon
Locking Feature: Patch Threads Or Pellet Threads Or Strip Threads Nominal Thread Diameter: 0.190 Inches Grip Length: 0.177 Inches Minimum And 0.197 Inches Maximum Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Material: Plastic Polyamide Locking Feature Material: Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp Material: Steel Overall Material Document And Classification: Steel Overall Material Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener Material Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener	Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Nominal Thread Diameter: Grip Length: 0.177 Inches Minimum And 0.197 Inches Maximum Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Material: Plastic Polyamide Locking Feature Material: Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8630 Fastener Or Steel Comp 8735 Fastener Or Steel Comp Material: Steel Overall Material Document And Classification: Mil-f-18240 Mil Spec Single Material Response Locking Feature Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification:	Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Grip Length: 0.177 Inches Minimum And 0.197 Inches Maximum Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Material: Plastic Polyamide Locking Feature Material: Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 8740	Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Features Provided: Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Material: Plastic Polyamide Locking Feature Material: Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 4130 Fastener Or Steel Comp 4037 Fastener Material: Material: Material Document And Classification: Mil-f-18240 Mil Spec Single Material Response Locking Feature Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Q-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener	Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch: Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Material: Plastic Polyamide Locking Feature Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 4130 Fastener Or Steel Comp 4037 Fastener Material: Steel Overall Material Document And Classification: Mil-f-18240 Mil Spec Single Material Response Locking Feature Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener	Grip Length:	0.177 Inches Minimum And 0.197 Inches Maximum
Minimum Tensile Strength: Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Material: Plastic Polyamide Locking Feature Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 4130 Fastener Or Steel Comp 4037 Fastener Material: Steel Overall Material Document And Classification: Mil-f-18240 Mil Spec Single Material Response Locking Feature Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener	Features Provided:	Finished Head
Hardness Rating: Material: Plastic Polyamide Locking Feature Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8630 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 4130 Fastener Or Steel Comp 4037 Fastener Material: Steel Overall Material Document And Classification: Mil-f-18240 Mil Spec Single Material Response Locking Feature Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener	Thread Quantity Per Inch:	32
Material:Plastic Polyamide Locking FeatureMaterial:Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8630 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 4130 Fastener Or Steel Comp 4037 FastenerMaterial:Steel OverallMaterial Document And Classification:Mil-f-18240 Mil Spec Single Material Response Locking FeatureSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Material: Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 4130 Fastener Or Steel Comp 4037 Fastener Material: Steel Overall Material Document And Classification: Mil-f-18240 Mil Spec Single Material Response Locking Feature Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material: Material: Steel Overall Material Document And Classification: Mil-f-18240 Mil Spec Single Material Response Locking Feature Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener	Material:	Plastic Polyamide Locking Feature
Material Document And Classification: Mil-f-18240 Mil Spec Single Material Response Locking Feature Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener	Material:	
Surface Treatment: Cadmium Fastener And Chromate Fastener Surface Treatment Document And Classification: Cadmium Fastener And Chromate Fastener Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener	Material:	Steel Overall
Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener	Material Document And Classification:	Mil-f-18240 Mil Spec Single Material Response Locking Feature
Classification: Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener	Surface Treatment:	Cadmium Fastener And Chromate Fastener
Thread Series Designator: Unf		Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener
	Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS21094-3003 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.