



Military-Fasteners.com

P/N MS21094-3003

Description

Fastener Length: 37/64", Thread: 10-32, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS210943003
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-194-3677
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21094-3003 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.381 Inches Minimum And 0.447 Inches Maximum
Fastener Length:	0.578 Inches Minimum And 0.624 Inches Maximum
Head Style:	Hexagon
Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.177 Inches Minimum And 0.197 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Plastic Polyamide Locking Feature
Material:	Steel Comp 4140 Fastener Or Steel Comp 8740 Fastener Or Steel Comp 8630 Fastener Or Steel Comp 8735 Fastener Or Steel Comp 4130 Fastener Or Steel Comp 4037 Fastener
Material:	Steel Overall
Material Document And Classification:	Mil-f-18240 Mil Spec Single Material Response Locking Feature
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS21094-3003> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.