



Military-Fasteners.com

P/N MS21095-3003

Description

Fastener Length: 37/64", Thread: 10-32, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS210953003
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-224-1355
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21095-3003 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.381 Inches Minimum And 0.447 Inches Maximum
Fastener Length:	0.578 Inches Minimum And 0.624 Inches Maximum
Head Style:	Hexagon
Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Locking Feature:	Patch Threads Or Strip Threads
End Item Identification:	Arleigh Burke Class Ddg;aircraft, (Ac-130h, Mc-130h, Ec-130e, Hc-13
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.177 Inches Minimum And 0.197 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Comp 431 Overall
Material Document And Classification:	Mil-s-18732 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS21095-3003> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.