



Military-Fasteners.com

P/N MS21096-08008

Description

Fastener Length: 61/64", Thread: 8-32, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS2109608008
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-455-2696
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS21096-08008 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.350 Inches Minimum And 0.478 Inches Maximum
Fastener Length:	0.922 Inches Minimum And 0.968 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Locking Feature:	Pellet Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Comp 8630 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-6050 Mil Spec 1st Material Response Overall Or Ams 6300 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS21096-08008> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.