

Description

Fastener Length: 61/64", Thread: 8-32, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS2109608008 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-00-455-2696 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS21096-08008 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.350 Inches Minimum And 0.478 Inches Maximum |
| Fastener Length: | 0.922 Inches Minimum And 0.968 Inches Maximum |
| Head Style: | Pan |
| Head Diameter: | 0.306 Inches Minimum And 0.322 Inches Maximum |
| Head Height: | 0.105 Inches Minimum And 0.115 Inches Maximum |
| Locking Feature: | Pellet Threads Or Strip Threads |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 8630 Overall Or Steel Comp 4037 Overall |
| Material Document And Classification: | Mil-s-6050 Mil Spec 1st Material Response Overall Or Ams 6300 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this socket head cap screw from our inventory online by visiting <https://military-fasteners.com/screws/socket+head+cap+screws/MS21096-08008> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.