

Description

Diameter: 13/64", steel comp 321 band

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | MS21122C15 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5340-01-291-0827 |

NO IMAGE
AVAILABLE

P/N MS21122C15 Specifications

| | |
|--|--|
| Tongue Hole Type: | Round, Unthreaded |
| Cushioning Environmental Protection: | Flame Resistant |
| Overall Width: | 0.485 Inches Minimum And 0.515 Inches Maximum |
| Diameter: | 0.204 Inches Nominal |
| Material Thickness: | 0.028 Inches Minimum And 0.036 Inches Maximum |
| Center To Center Distance Between Loop And Mounting Hole: | 0.905 Inches Minimum And 0.935 Inches Maximum |
| Distance From Loop Center To Tongue End: | 1.125 Inches Minimum And 1.153 Inches Maximum |
| Loop Inside Diameter: | 0.923 Inches Minimum And 0.953 Inches Maximum |
| Application/function: | M196.0 To P260.0 Deg C Temp Appl |
| Material: | Plastic Tetrafluoroethylene Cushion |
| Material: | Steel Comp 321 Band |
| Material Document And Classification: | L-p-403,type 1,class 1 Fed Spec Single Material Response Cushion |
| Material Document And Classification: | Mil-s-6721,comp Ti Or Cb,s32109 Mil Spec Single Material Response Band |
| Surface Treatment: | Passivate Band |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Band |
| Style Designator: | Offset Mount |
| Supplementary Features: | White Cushion W/ Red Stripe |
| Specification/standard Data: | 96906-ms21122 Government Standard |

How to Order

Order this clamp from our inventory online by visiting <https://military-fasteners.com/clamps/loop+clamps/MS21122C15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.