

Description

Fastener Length: 1-7/64", Thread: 1/4-28, Thread Length: 9/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS21125B411
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-092-6689
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS21125B411 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.277 Inches Minimum And 0.328 Inches Maximum
Fastener Length:	1.106 Inches Minimum And 1.126 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.477 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.126 Inches Minimum And 0.141 Inches Maximum
Locking Feature:	Detent Ball Fastener
Grip Diameter:	0.2487 Inches Minimum And 0.2492 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.688 Inches Minimum And 0.704 Inches Maximum
Thread Quantity Per Inch:	28
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.011 Inches Minimum First Hole And 1.031 Inches Maximum First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/MS21125B411> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.